



Configuration:

TECHNIQUE DATA SHEET

Pro-MicroScan #5822

Part Number	Description	Qty.
CAMA15822	[CAMERA TYPE] 2M Pixels eyepiece camera	1
CAMAC0058	[USB2.0 CABLE] High-Speed USB2.0 Cable with mini interface	1
CAMAC0011	[LENS COVER] Ø23.2mm rubber cover	1
CAMAC0012	[ADAPTOR] Ø23.2mm to Ø30.0mm, Ø23.2mm to Ø30.5mm	Optional
HARDWARE INFO. [SENSOR] 1/3" APTINA Color CMOS sensor		
[OPTIC SYSTEM] Simply, 400-650nm IR-cuter		
[DSP]Low cost Simply DSP w/o color engine		
Simply plastic tube Ø30 mm (D) X 63 mm (H)		
EVA/carton package 14.3 cm (L)X 9.8 cm (W) X 5.5 cm (H)		
Body Dia: 1.06" / 27 mm (D)		
Body Height: 1.80" / 45.8 mm (H)		
USB cable length: 59.1" / 1.5 m		
Weight(w/ USB cable): 0.18 lbs / 80 g		
Gross weight(Simply packing): 0.22 lbs / 100 g		
Gross weight(Standard packing): 0.55 lbs / 250 g		
PRODUCT INFO		

Pro-MicroScan #5822

Operating Environment	
Operating Temperature	0°C to 40°C(32°F to 104°F)
Storage Temperature	-20°C-60°C(-4°F to 140°F)
Operating Humidity	30%~90%
Storage Humidity	10%~90%
Power Supply	DC 5V from PC USB port
Hardware Informations	
Sensor MFG	APTINA (U.S.A)
Image Pickup Device	APTINA Super Color CMOS
Max.Resolution	Approx.2,000,000 Pixels
Recording System	Still Picture and Movie
Sensor Model	N/A
Sensor Size	1/3"
Optical Input Window	Fused silica
Pixel Size	2.8µm x 2.8µm
Video Mode	1600 x 1200 12fps,1280 x 1024,1280 x 960,800 x 600,640 x 480 30fps,352 x 288,320 x 240...
A/D	8bit
Peak Quantum Efficiency	20%
Dynamic Range	71dB
Sensitivity	1.0v/lux-sec @550nm
Spectral Range	380-1000nm(w/o IR cut) , 400-650nm (with IR cut)
Exposure Time	Automatic
Exposure	Electronic Rolling Snap(ERS)
ROI(Region of Interest)	N/A
Software Environment	
Operating System	Microsoft® Windows2003/XP/Vista/2008
Basic PC	32bit and 64bit
	CPU:Equal to Inter Pentium4 1.8GHz or higher
	Memory:512MB or more
	USB port:USB2.0 high speed port
	Display:17" or larger

